

电气性能 Electrical Characteristics SMR73 Series

Part No 产品编号	Test condition 测试条件	Inductance 电感 (μ H)	Toierance 公差 (%)	DC Resistance 直流电阻 (Ω) MAX	Rated DC current 额定电流 (A) MAX
SMR73-100M	1kHz/0.25V	10	±20	0.072	1.68
SMR73-120M	1kHz/0.25V	12	±20	0.098	1.52
SMR73-150M	1kHz/0.25V	15	±20	0.130	1.33
SMR73-180M	1kHz/0.25V	18	±20	0.140	1.20
SMR73-220M	1kHz/0.25V	22	±20	0.190	1.07
SMR73-270M	1kHz/0.25V	27	±20	0.21	0.96
SMR73-330M	1kHz/0.25V	33	±20	0.24	0.91
SMR73-390M	1kHz/0.25V	39	±20	0.32	0.77
SMR73-470M	1kHz/0.25V	47	±20	0.36	0.76
SMR73-560M	1kHz/0.25V	56	±20	0.47	0.68
SMR73-680M	1kHz/0.25V	68	±20	0.52	0.61
SMR73-820M	1kHz/0.25V	82	±20	0.69	0.57
SMR73-101M	1kHz/0.25V	100	±20	0.79	0.50
SMR73-121M	1kHz/0.25V	120	±20	0.89	0.49
SMR73-151M	1kHz/0.25V	150	±20	1.27	0.43
SMR73-181M	1kHz/0.25V	180	±20	1.45	0.39
SMR73-221M	1kHz/0.25V	220	±20	1.65	0.35
SMR73-271M	1kHz/0.25V	270	±20	2.31	0.32
SMR73-331M	1kHz/0.25V	330	±20	2.62	0.28
SMR73-391M	1kHz/0.25V	390	±20	2.94	0.26
SMR73-471M	1kHz/0.25V	470	±20	4.18	0.24
SMR73-561M	1kHz/0.25V	560	±20	4.67	0.22
SMR73-681M	1kHz/0.25V	680	±20	5.73	0.19
SMR73-821M	1kHz/0.25V	820	±20	6.54	0.18
SMR73-102M	1kHz/0.25V	1000	±20	9.44	0.16

※超出以上规格的特殊要求也可以满足。Special inquiries besides the above common used types can be meet.

电气性能 Electrical Characteristics SMR74 Series

Part No 产品编号	Test condition 测试条件	Inductance 电感 (μ H)	Toierance 公差 (%)	DC Resistance 直流电阻 (Ω) MAX	Rated DC current 额定电流 (A) MAX
SMR74-100M	1kHz/0.25V	10	±20	0.049	1.84
SMR74-120M	1kHz/0.25V	12	±20	0.058	1.71
SMR74-150M	1kHz/0.25V	15	±20	0.081	1.47
SMR74-180M	1kHz/0.25V	18	±20	0.091	1.31
SMR74-220M	1kHz/0.25V	22	±20	0.110	1.23
SMR74-270M	1kHz/0.25V	27	±20	0.15	1.12
SMR74-330M	1kHz/0.25V	33	±20	0.17	0.96
SMR74-390M	1kHz/0.25V	39	±20	0.23	0.91
SMR74-470M	1kHz/0.25V	47	±20	0.26	0.88
SMR74-560M	1kHz/0.25V	56	±20	0.35	0.75
SMR74-680M	1kHz/0.25V	68	±20	0.38	0.69
SMR74-820M	1kHz/0.25V	82	±20	0.43	0.61
SMR74-101M	1kHz/0.25V	100	±20	0.61	0.60
SMR74-121M	1kHz/0.25V	120	±20	0.66	0.52
SMR74-151M	1kHz/0.25V	150	±20	0.88	0.46
SMR74-181M	1kHz/0.25V	180	±20	0.98	0.42
SMR74-221M	1kHz/0.25V	220	±20	1.17	0.36
SMR74-271M	1kHz/0.25V	270	±20	1.64	0.34
SMR74-331M	1kHz/0.25V	330	±20	1.86	0.32
SMR74-391M	1kHz/0.25V	390	±20	2.85	0.29
SMR74-471M	1kHz/0.25V	470	±20	3.01	0.26
SMR74-561M	1kHz/0.25V	560	±20	3.62	0.23
SMR74-681M	1kHz/0.25V	680	±20	4.63	0.22
SMR74-821M	1kHz/0.25V	820	±20	5.20	0.20
SMR74-102M	1kHz/0.25V	1000	±20	6.00	0.18

※超出以上规格的特殊要求也可以满足。Special inquiries besides the above common used types can be meet.